# LF792 Datasheet

LOW-FLOW PRESSURE REGULATOR

# PRESSURE TECH

• Gas	🔵 Liquid 📔 🔵 Diaphrag	m 💿 Piston 📔 💿 Sel <sup>:</sup> Ver	f- Non- Vent Max Inlet: 1,034 bar (15,000 psi) Max Outlet: 1,034 bar (15,000 psi) C	Cv 0.1
	ĩ			



## **INTRODUCING THE LF792...**

The LF792 is a piston-sensed low-flow pressure regulator with a Tecasint<sup>®</sup> seat for use on high pressure gases. It uses a range of precision-machined sensing elements for pressure control up to 1,034 bar (15,000 psi) and offers the same great features as the LF692, but with enhanced support on the seat cartridge.

The LF792 features an unbalanced main valve as standard. Alternatively, a balanced option can be supplied.

## **SPECIFICATION**

Outlet Ranges	Up to 1,034 bar (15,000 psi)			
Design Broof Broonuro	150% max. working pressure (with R or S body materials)			
Design Floor Flessure	200% max. working pressure (with Q body material only)			
Seat Leakage	In accordance with ANSI/FCI 70-3			
Weight	4.5kg (9.9lbs)			

## STANDARD MATERIALS OF CONSTRUCTION

PART	MATERIALS
	ASTM A479 316/316L Stainless Steel (UNS S31600/S31603)
Body and Bonnet	ASTM A638/A638M 660 Type 1 Stainless Steel (UNS S66286)
	ASTM 17-4 PH Stainless Steel (UNS S17400)
Main Valve Pin	Inconel <sup>®</sup> 718 (UNS N07718)
Seat	Tecasint <sup>®</sup> (2011)
Valve Spring	ASTM A240 301 Stainless Steel (UNS S30100)
Piston	ASTM A479 316/316L Stainless Steel
Handwheel	Nylon
O-Rings	NBR N70 (Nitrile Buna N)
Loading Spring	Silicon Chrome Wire

Note: Pressure regulator rating may be limited by connection type, Cv and/or seat material. Contact the office for specific pressure or temperature requirements.

## FEATURES AND BENEFITS



2 ENHANCED SUPPORT ON THE SEAT

Offers prolonged service life.



Prevents deterioration to loading mechanism. Allows media to be piped off to return tank. Ideal for toxic or hazardous gases.



Simplified servicing through base of regulator.

#### PRESSURE TECH LTD

Unit 24, Graphite Way, Hadfield, Glossop, Derbyshire, UK, SK13 1QH +44 (0)1457 899 307 | <u>sales@pressure-tech.com</u> | <u>www.pressure-tech.com</u> **DESIGNED, MANUFACTURED AND BUILT IN THE UK** © 2025 Pressure Tech Ltd. All Rights Reserved.

Product availability and specifications contained herein are subject to change without notice. Consult local distributor or factory for potential revisions and/or service related issues Pressure Tech Ltd support with product selection recommendations only - it is the users responsibility to ensure the product is suitable for their specific application requirements.





## DRAWINGS AND INSTALLATION DIMENSIONS

Dimensions shown for 1/4" NPT option and standard configurations only - please contact the office for other options.



Product availability and specifications contained herein are subject to change without notice. Consult local distributor or factory for potential revisions and/or service related issues. Pressure Tech Ltd support with product selection recommendations only - it is the users responsibility to ensure the product is suitable for their specific application requirements.



PRESSURE TECH LTD Unit 24, Graphite Way, Hadfield, Glossop, Derbyshire, UK, SK13 1QH +44 (0)1457 899 307 | sales@pressure-tech.com | www.pressure-tech.com DESIGNED, MANUFACTURED AND BUILT IN THE UK © 2025 Pressure Tech Ltd. All Rights Reserved.





## FLOW CURVE

Please contact the office for further information.

## PORTING CONFIGURATIONS



Note:

Additional porting configurations are available - please contact the office for further information.

Product availability and specifications contained herein are subject to change without notice. Consult local distributor or factory for potential revisions and/or service related issues Pressure Tech Ltd support with product selection recommendations only - it is the users responsibility to ensure the product is suitable for their specific application requirements.



 PRESSURE TECH LTD

 Unit 24, Graphite Way, Hadfield, Glossop, Derbyshire, UK, SK13 1QH

 +44 (0)1457 899 307
 sales@pressure-tech.com

 DESIGNED, MANUFACTURED AND BUILT IN THE UK

 © 2025 Pressure Tech Ltd. All Rights Reserved.



## **LF792 Datasheet**

LOW-FLOW PRESSURE REGULATOR



s ● Liquid ● Diaphragm ● Piston ● Self- ● Non- Vent ● Vent Max Inlet	: 1,034 bar (15,000 psi) Max Outlet: 1,034 bar (15,000 psi) Cv						
<b>DRDERING INFORMATION</b> To build a Pressure Tech part number, simply combine the characters identified below in sequence:							
LF792 - 01 - S - 690S - N - 03A - N - NV - XXX							
REGULATOR	MODIFICATIONS*						
LF792	Contact the office for information.						
CV VALUE	VENTING						
05 – 0.05 01 – 0.1 03 – 0.3 (Balanced Design Only)	SV – Self-Venting (Captured) NV – Non-Venting						
	PORTING CONFIGURATION						
S – ASTM A479 316/316L Stainless Steel Q – ASTM A638/A638M 660 Type 1 Stainless Steel	N - No gauge ports Refer to page 3 for porting options.						
R - ASTM 17-4 PH Stainless Steel <b>Not for Hydrogen Gas</b> and from 690 bar (10,000psi) to 1,034 bar (15,000 psi) inlet pressure only	INLET/OUTLET CONNECTION** 02A – 1/4" Medium Pressure 02N – 1/4" NPT <sup></sup>						
CONTROL PRESSURE	03N – 3/8" NPT****						
50 – Up to 50 bar (725 psi) 100 – Up to 100 bar (1,450 psi) 140 – Up to 140 bar (2020 psi)***	04A – 9/16" Medium Pressure 04N – 1/2" NPT <sup></sup>						
200 – Up to 200 bar (2,900 psi)	O-RING MATERIAL**						
414 – Up to 414 bar (6,000 psi) 600 – Up to 600 bar (8,700 psi)*** 690 – Up to 690 bar (10,000 psi) 1034 – Up to 1,034 bar (15,000 psi)	H – HNBR N – NBR V – FKM/FPM W – FKM/FPM (Low Temp & AED)						
LOADING MECHANISM							
S – Spring-Loaded A – Air-Loaded							

OPTIONAL EXTRAS					
Service Kit	SRK-LF792	Various options available			
Panel Mounting Ring	PT-C-061-003-RING	Stainless Steel panel mount ring			
Panel Mounting Ring	PT-C-061-003-001-RING	Aluminium panel mount ring			
Note: Ancillary equipment also available.					

TRADEMARK: Tecasint<sup>®</sup> is a registered trademark of Ensinger GmbH

\* Where applicable \*\* Other connections/materials may be available

\*\*\*\* Air-loaded only \*\*\*\* Max. 690 bar (10,000 psi) supply pressure on NPT - use MP for higher pressures

Product availability and specifications contained herein are subject to change without notice. Consult local distributor or factory for potential revisions and/or service related issues. Pressure Tech Ltd support with product selection recommendations only - it is the users responsibility to ensure the product is suitable for their specific application requirements.

DNV

## PRESSURE TECH LTD

Unit 24, Graphite Way, Hadfield, Glossop, Derbyshire, UK, SK13 1QH +44 (0)1457 899 307 | sales@pressure-tech.com | www.pressure-tech.com DESIGNED, MANUFACTURED AND BUILT IN THE UK © 2025 Pressure Tech Ltd. All Rights Reserved.

