


SGP Datasheet

SPECIALITY GAS POINT OF USE GAS MANIFOLD

PRESSURE TECH

● Gas ● Liquid | ● Diaphragm ● Piston | ● Self-Venting ● Non-Venting | Max Inlet: 40 bar (580 psi) | Max Outlet: 10 bar (145 psi) | Cv 0.1



INTRODUCING THE SGP...

The SGP is a point of use gas manifold, mounted onto a stainless steel panel (as standard), for speciality gases with a maximum purity of 6.0. They are designed to accurately reduce the incoming gas supply from a maximum of 40 bar (580 psi) inlet pressure to a safe and usable level at the point-of-use.

Typical applications include gas supply to analytical instruments and engine emission testing for automotive industries.

The SGP consists of a pressure regulator, and an optional upstream shut-off valve, outlet gauge, and relief valve. The inlet connection is 1/4" female NPT.

STANDARD MATERIALS OF CONSTRUCTION

PART	MATERIALS
Body and Bonnet	ASTM A479 316/316L Stainless Steel (UNS S31600/S31603)
	Chrome Plated Brass CW614N (UNS C38500)
Main Valve Pin	Hastelloy C276® (UNS N10276)
Soft Seat	PCTFE (KeI-F)
Valve Spring	Inconel® X750 (UNS N07750)
Diaphragm	Hastelloy C22® (UNS N06022)
Handwheel	Anodised Aluminium
O-Rings	FKM/FPM (Viton)
Loading Spring	Spring Steel Grade 80 BS 1449
Filter	100 Microns

Note: Pressure regulator rating may be limited by connection type, Cv and/or seat material. Contact the office for specific pressure or temperature requirements.

SPECIFICATIONS

Max. Inlet	40 bar (580 psi)
Max. Outlet	Up to 10 bar (145 psi)
Cv	0.1
Design Proof Pressure	150% max. working pressure
Seat Leakage	< 1×10 E-6 mbar L/s (Helium)
External Leakage	< 1×10 E-9 mbar L/s (Helium)
Purity	≥ 6.0
Min/Max Temperatures	-25°C to +70°C (-13°F to 158°F)
Weights	2.4kg (5.3lbs)
Dimensions	See page 2

Note: Unless otherwise requested, the relief valve's set pressure will be 120% of the regulator's nominal outlet set pressure.

FEATURES AND BENEFITS

1 FOR HIGH PURITY GAS ≥6.0

Ensures the materials, design, and internal surface finish do not contaminate HP gases.

2 ERGONOMIC DESIGN

Handwheel and body shape makes it easier for technicians to adjust pressures.

3 OPTIONAL OUTLET PRESSURE RELIEF VALVE

Automatically vents gas if downstream pressure rises above required levels.

4 LOW-PROFILE DESIGN

Compact dimensions are perfect when space is limited.

Product availability and specifications contained herein are subject to change without notice. Consult local distributor or factory for potential revisions and/or service related issues. Pressure Tech Ltd support with product selection recommendations only - it is the users responsibility to ensure the product is suitable for their specific application requirements.



PRESSURE TECH LTD

Unit 24, Graphite Way, Hadfield, Glossop, Derbyshire, UK, SK13 1QH

+44 (0)1457 899 307 | sales@pressure-tech.com | www.pressure-tech.com

DESIGNED, MANUFACTURED AND BUILT IN THE UK

© 2026 Pressure Tech Ltd. All Rights Reserved.

020326

PAGE:
1 OF 5

SGP Datasheet

SPECIALITY GAS POINT OF USE GAS MANIFOLD




● Gas ● Liquid | ● Diaphragm ● Piston | ● Self-Venting ● Non-Venting | Max Inlet: 40 bar (580 psi) | Max Outlet: 10 bar (145 psi) | Cv 0.1

CLEANLINESS STANDARDS & SURFACE FINISH

All components are precision-cleaned to meet stringent cleanliness levels of 1mg/m², in accordance with ASTM G93/G93M, ASTM F331-13, and ISO 15001:2011. Brass products are electroplated as standard to enhance durability and corrosion resistance.

DRAWINGS AND INSTALLATION DIMENSIONS

Mounted on stainless-steel panel:



Product availability and specifications contained herein are subject to change without notice. Consult local distributor or factory for potential revisions and/or service related issues. Pressure Tech Ltd support with product selection recommendations only - it is the users responsibility to ensure the product is suitable for their specific application requirements.



PRESSURE TECH LTD

Unit 24, Graphite Way, Hadfield, Glossop, Derbyshire, UK, SK13 1QH

+44 (0)1457 899 307 | sales@pressure-tech.com | www.pressure-tech.com

DESIGNED, MANUFACTURED AND BUILT IN THE UK

© 2026 Pressure Tech Ltd. All Rights Reserved.

020326

PAGE:
2 OF 5

SGP Datasheet


SPECIALITY GAS POINT OF USE GAS MANIFOLD



Gas
 Liquid
 Diaphragm
 Piston
 Self-Venting
 Non-Venting
 Max Inlet: 40 bar (580 psi)
 Max Outlet: 10 bar (145 psi)
 Cv 0.1

DRAWINGS AND INSTALLATION DIMENSIONS

Alternative standalone option:



Product availability and specifications contained herein are subject to change without notice. Consult local distributor or factory for potential revisions and/or service related issues. Pressure Tech Ltd support with product selection recommendations only - it is the users responsibility to ensure the product is suitable for their specific application requirements.



PRESSURE TECH LTD

Unit 24, Graphite Way, Hadfield, Glossop, Derbyshire, UK, SK13 1QH

+44 (0)1457 899 307 | sales@pressure-tech.com | www.pressure-tech.com

DESIGNED, MANUFACTURED AND BUILT IN THE UK

© 2026 Pressure Tech Ltd. All Rights Reserved.

020326

PAGE:
3 OF 5


SGP Datasheet

SPECIALITY GAS POINT OF USE GAS MANIFOLD



● Gas ● Liquid | ● Diaphragm ● Piston | ● Self-Venting ● Non-Venting | Max Inlet: 40 bar (580 psi) | Max Outlet: 10 bar (145 psi) | Cv 0.1

P&ID




- A: Upstream shut-off valve
- B: Pressure regulator
- C: Outlet pressure gauge
- D: Relief valve

FLOW CURVE

The flow charts for line pressure regulators have been generated in accordance with ISO 2503 which requires the upstream pressure to be approximately twice that of the downstream pressure.

PORTING CONFIGURATIONS



Product availability and specifications contained herein are subject to change without notice. Consult local distributor or factory for potential revisions and/or service related issues. Pressure Tech Ltd support with product selection recommendations only - it is the users responsibility to ensure the product is suitable for their specific application requirements.



PRESSURE TECH LTD

Unit 24, Graphite Way, Hadfield, Glossop, Derbyshire, UK, SK13 1QH

+44 (0)1457 899 307 | sales@pressure-tech.com | www.pressure-tech.com

DESIGNED, MANUFACTURED AND BUILT IN THE UK

© 2026 Pressure Tech Ltd. All Rights Reserved.

020326

PAGE:
4 OF 5

SGP Datasheet


SPECIALITY GAS POINT OF USE GAS MANIFOLD



Gas
 Liquid
 Diaphragm
 Piston
 Self-Venting
 Non-Venting
 Max Inlet: 40 bar (580 psi)
 Max Outlet: 10 bar (145 psi)
 Cv 0.1

ORDERING INFORMATION

To build a Pressure Tech part number, simply combine the characters identified below in sequence:



TRADEMARKS: Inconel® is a registered trademark of Inco Alloys International
 Hastelloy® is a registered trademark of Haynes International, Inc

Product availability and specifications contained herein are subject to change without notice. Consult local distributor or factory for potential revisions and/or service related issues.
 Pressure Tech Ltd support with product selection recommendations only - it is the users responsibility to ensure the product is suitable for their specific application requirements.



PRESSURE TECH LTD

Unit 24, Graphite Way, Hadfield, Glossop, Derbyshire, UK, SK13 1QH
 +44 (0)1457 899 307 | sales@pressure-tech.com | www.pressure-tech.com

DESIGNED, MANUFACTURED AND BUILT IN THE UK

© 2026 Pressure Tech Ltd. All Rights Reserved.

020326

PAGE:
5 OF 5