



Hydrogen	LW351 IN 350 bar OUT 3 bar CV 0.06 drones			CV414-SC RATING 414 bar OUT N/A bar CV 0.06 gas cylinders & drones TPED APPROVED			AUTO438 IN 438 bar OUT 20 bar CV 0.25 vehicles DESIGNED TO EC79 STANDARDS		
	A875 IN 875 bar OUT 30 bar CV 0.35 / 0.5 vehicles			H875 IN 875 bar OUT 100 bar CV 0.5 vehicles			M875 IN 875 bar OUT 60 bar CV 0.35 / 0.5 vehicles		
	RF1034 IN 1034 bar OUT 1034 bar CV 0.5 / 1.0 refuelling			LW438 IN 438 bar OUT 20 bar CV 0.06 material handling			LW-TS414 IN 414 bar OUT 1 bar CV 0.06 mobility		
	BP301 RATING 150 bar OUT 150 bar CV 0.1 electrolysers			AVC/AVO690 IN 690 bar OUT 690 bar CV 0.8 / 2.0 isolation			AVC/AVO1034 IN 1034 bar OUT 1034 bar CV 0.8 isolation		
Back Pressure	BP010 RATING 10 bar OUT 5 bar CV 0.1 back pressure			BP300 RATING 35 bar OUT 20 bar CV 0.1 back pressure			BP301 RATING 150 bar OUT 150 bar CV 0.1 back pressure		
	BP-LF540 RATING 414 bar OUT 414 bar CV 0.1 low-flow			BP-LF690 RATING 550 bar OUT 414 bar CV 0.1/0.02/0.06 low-flow			BP-LF691 RATING 1034 bar OUT 900 bar CV 0.1 / 0.02 low-flow		
	BP-MF400 RATING 10 bar OUT 10 bar CV 3.0 medium-flow			BP-MF401 RATING 400 bar OUT 200 bar CV 3.0 medium-flow			BP-MF690 (05) RATING 550 bar OUT 414 bar CV 0.5 medium-flow		
	BP-MF690 (15) RATING 690 bar OUT 300 bar CV 1.5 medium-flow			BP-MF691 (05) RATING 690 bar OUT 690 bar CV 0.5 medium-flow					

Product Overview

Analyser & Instrumentation

Analyser & Instrumentation	● ○ auto-changeover	ACS101  IN 300 bar OUT 20 bar CV 0.5	● ○ auto-changeover	ACS240  IN 300 bar OUT 10 bar CV 0.06	● ○ auto-changeover	ACS310  IN 300 bar OUT 20 bar CV 0.06	
● ○ auto-changeover	ACU310  IN 300 bar OUT 20 bar CV 0.06	● ○ cylinder assembly	CYL310  IN 414 bar OUT 35 bar CV 0.06	● ○ cylinder assembly	CYL540  IN 550 bar OUT 414 bar CV 0.1	● ○ compact	MINI300  IN 300 bar OUT 100 bar CV 0.06
● ○ low-flow	LF240  IN 414 bar OUT 10 bar CV 0.06	● ○ low-flow	LF310  IN 414 bar OUT 35 bar CV 0.06 / 0.15	● ○ two-stage	TS310  IN 414 bar OUT 25 bar CV 0.06	● ○ two-stage	TS311  IN 414 bar OUT 20 bar CV 0.06
● ● heated manifold	XHM410  IN 300 bar OUT N/A CV N/A 	● ○ single heated	XHS410  IN 414 bar OUT 35 bar CV 0.06 	● ○ single heated	XHS411  IN 414 bar OUT 150 bar CV 0.06 		
● ● electric heated	XHR310  IN 414 bar OUT 35 bar CV 0.06 	● ● steam heated	XHR310  IN 414 bar OUT 35 bar CV 0.06	● ● electric heated	XHR311  IN 414 bar OUT 150 bar CV 0.06 		

KEY

gas
liquid

MANUFACTURER

PRESSURE TECH LTD
Unit 24, Graphite Way, Glossop, UK, SK13 1QH
T +44 (0)1457 899 307
E sales@pressure-tech.com
W www.pressure-tech.com

KEY

gas
liquid

Low-Flow			LF311			LF540			LF792			Hydraulic			LGC690			MF414H			HYD690											
			low-flow  IN 414 bar OUT 180 bar CV 0.06	low-flow  IN 690 bar OUT 414 bar CV 0.1	low-flow  IN 1034 bar OUT 1034 bar CV 0.1 / 0.3 / 0.05	logic control  IN 414 bar OUT 20 bar CV 0.3	medium-flow  IN 414 bar OUT 414 bar CV 2.0	hydraulic  IN 690 bar OUT 690 bar CV 0.06																								
Medium-Flow			MF101			MF230			MF231			MF210			HYD691			LF690			DF1034			LF691								
			medium-flow  IN 414 bar OUT 40 bar CV 0.5	medium-flow  IN 230 bar OUT 10 bar CV 1.0	medium-flow  IN 230 bar OUT 100 bar CV 1.0	medium-flow  IN 40 bar OUT 10 bar CV 1.8	hydraulic  IN 690 bar OUT 690 bar CV 0.06	low-flow  IN 690 bar OUT 690 bar CV 0.05 / 0.1 / 0.3	dual-flow  PATENT PENDING PATENT PENDING IN 1380 bar OUT 1380 bar CV 1.5 & 0.06	low-flow  IN 1380 bar OUT 1380 bar CV 0.05 / 0.1 / 0.3																						
Medium-Flow			MF301			MF400			MF401			MF414			Diving			BIBS100			LF310			LF540								
			medium-flow  IN 300 bar OUT 300 bar CV 2.0	medium-flow  IN 400 bar OUT 10 bar CV 2.0	medium-flow  IN 400 bar OUT 400 bar CV 2.0	medium-flow  IN 414 bar OUT 414 bar CV 2.0	negative-biased  RATING 50 bar OUT 30 bar CV 2.0	low-flow  IN 414 bar OUT 35 bar CV 0.06 / 0.15	low-flow  IN 690 bar OUT 414 bar CV 0.1																							
High-Flow			HF211			HF250			HF251			MF101D			MF300T			MF301D														
			high-flow  IN 210 bar OUT 200 bar CV 13.0	high-flow  IN 250 bar OUT 10 bar CV 7.0	high-flow  IN 250 bar OUT 200 bar CV 7.0	medium-flow  IN 300 bar OUT 40 bar CV 0.5	medium-flow  IN 300 bar OUT 25 bar CV 2.0	medium-flow  IN 300 bar OUT 300 bar CV 2.0																								
High-Flow			HF300			HF301			HF600			Subsea			SS-BP400			SS-COM301			SS231			SS414			SS690			SS691		
			high-flow  IN 300 bar OUT 10 bar CV 4.0	high-flow  IN 300 bar OUT 300 bar CV 4.0 bar	high-flow  IN 600 bar OUT 600 bar CV 7.0 bar	subsea  IN 400 bar OUT 10 bar CV 2.0	subsea  IN 300 bar OUT 50 bar CV 0.5	subsea  IN 230 bar OUT 35 bar CV 1.0	subsea  IN 414 bar OUT 250 bar CV 2.0	subsea  API 17F APPROVED IN 690 bar OUT 690 bar CV 0.1	subsea  IN 1034 bar OUT 690 bar CV 0.1																					