

**Hydrogen**

**LW351**



drone

| IN      | OUT   | CV   |
|---------|-------|------|
| 350 bar | 3 bar | 0.06 |

**CV414-SC**



gas cylinders & drones



| RATING  | OUT     | CV   |
|---------|---------|------|
| 414 bar | N/A bar | 0.06 |

**AUTO438**



vehicles

| IN      | OUT    | CV   |
|---------|--------|------|
| 438 bar | 20 bar | 0.25 |

**A875**



vehicles

| IN      | OUT    | CV         |
|---------|--------|------------|
| 700 bar | 30 bar | 0.35 / 0.5 |

**H875**



vehicles

| IN      | OUT     | CV  |
|---------|---------|-----|
| 700 bar | 100 bar | 0.5 |

**M875**



vehicles

| IN      | OUT    | CV         |
|---------|--------|------------|
| 700 bar | 60 bar | 0.35 / 0.5 |

**RF1034**



refuelling

| IN       | OUT      | CV        |
|----------|----------|-----------|
| 1034 bar | 1034 bar | 0.5 / 1.0 |

**LW438**



material handling

| IN      | OUT    | CV   |
|---------|--------|------|
| 438 bar | 20 bar | 0.06 |

**LW-TS414**



mobility

| IN      | OUT   | CV   |
|---------|-------|------|
| 414 bar | 1 bar | 0.06 |

**BP301**



electrolysers

| RATING  | OUT     | CV  |
|---------|---------|-----|
| 150 bar | 150 bar | 0.1 |

**AVC/AVO690**



isolation

| IN      | OUT     | CV        |
|---------|---------|-----------|
| 690 bar | 690 bar | 0.8 / 2.0 |

**AVC/AVO1034**



isolation

| IN       | OUT      | CV  |
|----------|----------|-----|
| 1034 bar | 1034 bar | 0.8 |

**Back Pressure**

**BP010**



low-flow

| RATING | OUT   | CV  |
|--------|-------|-----|
| 10 bar | 5 bar | 0.1 |

**BP300**



low-flow

| RATING | OUT    | CV  |
|--------|--------|-----|
| 35 bar | 20 bar | 0.1 |

**BP301**



low-flow

| RATING  | OUT     | CV  |
|---------|---------|-----|
| 150 bar | 150 bar | 0.1 |

**BP-LF2KH**



low-flow

| RATING    | OUT       | CV  |
|-----------|-----------|-----|
| 2,068 bar | 2,068 bar | 0.1 |

**BP-LF540**



low-flow

| RATING  | OUT     | CV  |
|---------|---------|-----|
| 414 bar | 414 bar | 0.1 |

**BP-LF690**



low-flow

| RATING  | OUT     | CV            |
|---------|---------|---------------|
| 550 bar | 414 bar | 0.1/0.02/0.06 |

**BP-LF691**



low-flow

| RATING   | OUT     | CV         |
|----------|---------|------------|
| 1034 bar | 900 bar | 0.1 / 0.02 |

**BP-MF400**



medium-flow

| RATING | OUT    | CV  |
|--------|--------|-----|
| 10 bar | 10 bar | 3.0 |

**BP-MF401**



medium-flow

| RATING  | OUT     | CV  |
|---------|---------|-----|
| 400 bar | 200 bar | 3.0 |

**BP-MF690 (05)**



medium-flow

| RATING  | OUT     | CV  |
|---------|---------|-----|
| 550 bar | 414 bar | 0.5 |

**BP-MF690 (15)**



medium-flow

| RATING  | OUT     | CV  |
|---------|---------|-----|
| 690 bar | 300 bar | 1.5 |

**BP-MF691 (05)**



medium-flow

| RATING  | OUT     | CV  |
|---------|---------|-----|
| 690 bar | 690 bar | 0.5 |

**KEY**

- gas
- liquid

**MANUFACTURER**

**PRESSURE TECH LTD**

Units 1-2, Graphite Way, Glossop, UK, SK13 1QH

T +44 (0)1457 899 307

E [sales@pressure-tech.com](mailto:sales@pressure-tech.com)

W [www.pressure-tech.com](http://www.pressure-tech.com)




16 JUN 2026

**Product Overview**

**Analysers & Inst.**


**ACS101**



auto-changeover

| IN      | OUT    | CV  |
|---------|--------|-----|
| 300 bar | 20 bar | 0.5 |

**ACS240**



auto-changeover

| IN      | OUT    | CV   |
|---------|--------|------|
| 300 bar | 10 bar | 0.06 |

**ACS310**



auto-changeover

| IN      | OUT    | CV   |
|---------|--------|------|
| 300 bar | 20 bar | 0.06 |

**ACU310**



auto-changeover

| IN      | OUT    | CV   |
|---------|--------|------|
| 300 bar | 20 bar | 0.06 |

**CYL310**



cylinder assembly

| IN      | OUT    | CV   |
|---------|--------|------|
| 414 bar | 35 bar | 0.06 |

**CYL540**



cylinder assembly

| IN      | OUT     | CV  |
|---------|---------|-----|
| 550 bar | 414 bar | 0.1 |

**LF240**



compact

| IN      | OUT    | CV   |
|---------|--------|------|
| 414 bar | 10 bar | 0.06 |

**LF310**



low-flow

| IN      | OUT    | CV        |
|---------|--------|-----------|
| 414 bar | 35 bar | 0.06/0.15 |

**MINI300**



low-flow

| IN      | OUT     | CV   |
|---------|---------|------|
| 300 bar | 100 bar | 0.06 |

**TS310**



two-stage

| IN      | OUT    | CV   |
|---------|--------|------|
| 414 bar | 25 bar | 0.06 |

**TS311**



two-stage

| IN      | OUT    | CV   |
|---------|--------|------|
| 414 bar | 20 bar | 0.06 |

**XHM410**



heated manifold

| IN      | OUT | CV  |
|---------|-----|-----|
| 300 bar | N/A | N/A |

**XHS410**



single heated

| IN      | OUT    | CV   |
|---------|--------|------|
| 414 bar | 35 bar | 0.06 |

**XHS411**



single heated

| IN      | OUT     | CV   |
|---------|---------|------|
| 414 bar | 150 bar | 0.06 |

**XHR310**



electric heated

| IN      | OUT    | CV   |
|---------|--------|------|
| 414 bar | 35 bar | 0.06 |

**XHR310**



steam heated

| IN      | OUT    | CV   |
|---------|--------|------|
| 414 bar | 35 bar | 0.06 |

**XHR311**




electric heated

| IN      | OUT     | CV   |
|---------|---------|------|
| 414 bar | 150 bar | 0.06 |

**Speciality Gas**

**SGA**



semi-auto changeover

| IN      | OUT    | CV  |
|---------|--------|-----|
| 300 bar | 50 bar | 0.1 |

**SGC**



cylinder regulator

| IN      | OUT    | CV  |
|---------|--------|-----|
| 300 bar | 50 bar | 0.1 |

**SGL**



line regulator

| IN      | OUT    | CV  |
|---------|--------|-----|
| 300 bar | 50 bar | 0.1 |

**SGM**



manual changeover

| IN      | OUT    | CV  |
|---------|--------|-----|
| 300 bar | 50 bar | 0.1 |

**SGP**



point-of-use

| IN     | OUT    | CV  |
|--------|--------|-----|
| 50 bar | 14 bar | 0.1 |

**KEY**

- gas
- liquid

Low-Flow

|   |   |   |
|---|---|---|
| <b>LF311</b>  | <b>LF540</b>  | <b>LF792</b>  |
|  |  |  |
| IN 414 bar<br>OUT 180 bar<br>CV 0.06  | IN 690 bar<br>OUT 414 bar<br>CV 0.1   | IN 1034 bar<br>OUT 1034 bar<br>CV 0.1 / 0.3 / 0.05                                  |








Hydraulic

|   |   |   |
|---|---|---|
| <b>LGC690</b>   | <b>MF414H</b>   | <b>HYD690</b>   |
|  |  |  |
| IN 414 bar<br>OUT 20 bar<br>CV 0.3  | IN 414 bar<br>OUT 414 bar<br>CV 2.0   | IN 690 bar<br>OUT 690 bar<br>CV 0.06  |

Medium-Flow

|   |   |  |   |   |   |   |   |
|---|---|--|---|---|---|---|---|
| <b>MF101</b>  | <b>MF230</b>  | <b>MF231</b>   | <b>MF210</b>  | <b>HYD691</b>   | <b>LF690</b>  | <b>DF1034</b>   | <b>LF691</b>  |
|  |  |  |  |  |  |  |  |
| IN 414 bar<br>OUT 40 bar<br>CV 0.5  | IN 230 bar<br>OUT 10 bar<br>CV 1.0  | IN 230 bar<br>OUT 100 bar<br>CV 1.0  | IN 40 bar<br>OUT 10 bar<br>CV 1.8   | IN 690 bar<br>OUT 690 bar<br>CV 0.06  | IN 690 bar<br>OUT 690 bar<br>CV 0.05 / 0.1 / 0.3                                    | IN 1380 bar<br>OUT 1380 bar<br>CV 1.5 & 0.06  | IN 1380 bar<br>OUT 1380 bar<br>CV 0.05 / 0.1 / 0.3                                  |










Diving

|  |  |   |  |  |  |  |
|--|--|---|--|--|--|--|
| <b>MF301</b>   | <b>MF400</b>   | <b>MF401</b>  | <b>MF414</b>   | <b>BIBS100</b>   | <b>LF310</b>   | <b>LF540</b>   |
|  |  |  |  |  |  |  |
| IN 300 bar<br>OUT 300 bar<br>CV 2.0  | IN 400 bar<br>OUT 10 bar<br>CV 2.0   | IN 400 bar<br>OUT 400 bar<br>CV 2.0   | IN 414 bar<br>OUT 414 bar<br>CV 2.0  | RATING 50 bar<br>OUT 30 bar<br>CV 2.0  | IN 414 bar<br>OUT 35 bar<br>CV 0.06 / 0.15   | IN 690 bar<br>OUT 414 bar<br>CV 0.1  |

High-Flow

|   |  |   |   |   |   |
|---|--|---|---|---|---|
| <b>HF211</b>  | <b>HF250</b>   | <b>HF251</b>  | <b>MF101D</b>   | <b>MF300T</b>   | <b>MF301D</b>   |
|  |  |  |  |  |  |
| IN 210 bar<br>OUT 200 bar<br>CV 13.0  | IN 250 bar<br>OUT 10 bar<br>CV 7.0   | IN 250 bar<br>OUT 200 bar<br>CV 7.0   | IN 300 bar<br>OUT 40 bar<br>CV 0.5  | IN 300 bar<br>OUT 25 bar<br>CV 2.0  | IN 300 bar<br>OUT 300 bar<br>CV 2.0   |

Subsea

|   |   |   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|---|---|
| <b>HF300</b>  | <b>HF301</b>  | <b>HF600</b>  | <b>SS-BP400</b>   | <b>SS-COM301</b>  | <b>SS231</b>  | <b>SS414</b>  | <b>SS690</b>  | <b>SS691</b>  |
|  |  |  |  |  |  |  |  |  |
| IN 300 bar<br>OUT 10 bar<br>CV 4.0  | IN 300 bar<br>OUT 300 bar<br>CV 4.0   | IN 600 bar<br>OUT 600 bar<br>CV 7.0   | IN 400 bar<br>OUT 10 bar<br>CV 2.0  | IN 300 bar<br>OUT 50 bar<br>CV 0.5  | IN 230 bar<br>OUT 35 bar<br>CV 1.0  | IN 414 bar<br>OUT 250 bar<br>CV 2.0   | IN 690 bar<br>OUT 690 bar<br>CV 0.1   | IN 1034 bar<br>OUT 690 bar<br>CV 0.1  |

KEY  
● gas  
● liquid

KEY  
● gas  
● liquid